

## DS-1100KI Network Keyboard



### Key Features

- 7" TFT touch screen at 800x480 resolution
- Speed dome, video decoder & DVR control
- 1-ch HD video stream decoding at 1080p
- Support 15 users, and each can operate up to 256 devices
- USB 2.0 interface for video backup

104-759  
DS-1100KI

### Specifications

DS-1100KI	
<b>Audio Input/Output</b>	
Line in	1-ch, 3.5 mm connector (2.0 Vp-p, 1 kΩ)
Audio out	1-ch, 3.5 mm connector (Linear, 560 Ω)
<b>External Interface</b>	
Network interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface
RS-232 interface	1 RS-232 interface (for parameters configuration and maintenance)
RS-485 interface	1 RS-485 interface
USB interface	1, USB2.0 (for data storage and device upgrade)
<b>General</b>	
LCD	Resolution: 800 × 480
Power supply	12 VDC
Power consumption	≤ 15W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Dimensions (W × D × H)	110 × 193 × 435 mm
Weight	2 kg



Innovative Electronic Solutions  
www.ness.com.au



NSW Ph 02 8825 9222 sales@ness.com.au | VIC Ph 03 9875 6400 nessmelb@ness.com.au | QLD Ph 07 3399 4910 nessbris@ness.com.au | WA Ph 08 9328 2511 nessper@ness.com.au | SA Ph 08 8152 0000 adelaide@ness.com.au