

DS-PDMCS-EG2-WB

Wireless Slim Magnet Detector

114-262

DS-PDMCS-EG2-WB is a wireless opening detector that notifies of first signs of room intrusion by means of a broken door or window, slim design specially used in window frames for vanishing installation.

- Slim design for an unobtrusive (unnoticeable) installation
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission



Specifications

	Model	DS-PDMCS-EG2-WB
Detection Performance	Detection Method	Opening Contact
	Detection Gap	52 mm Max
Feature	Digital Processing	Support
	Tamper Protection	Front, Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	Power Switch	Power Up Enrolling
	LED Indicator	Blue (Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	433 MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1 Km
	Frequency Hopping	Support
Electrical Characteristics	Enrolling Method	Power up,Remote ID,QR Code
	Power Supply	Battery Powered
	Battery Type	CR2450 x 1
	Typical Voltage	3 V
General	Standard Battery Life	3 Years
	Operation Temperature	10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(WxHxD)	Sensor: 29 mm × 69 mm × 10 mm Magnetic Stick: 14 mm × 69 mm × 10 mm
	Weight	38 g
	Application Scenario	Indoor

ORDERING INFORMATION

114-262

Hikvision AX PRO Series Wireless Slim Magnetic Contact



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au