

DS-PDEB2-EG2-WB

Wireless Emergency Button

114-264

The panic button is an effective wireless product for emergency. It is flexible to be fixed in any hidden places.



- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Effective emergency button
- Frequency hopping against jamming for reliable transmission

Specifications

Model		DS-PDEB2-EG2-WB
Feature	Button	2
	Tamper Protection	Front, Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	LED Indicator	Blue (Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	433 MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	800 m
	Frequency Hopping	Support
	Enrolling Method	Power up, Remote ID, QR Code
Electrical Characteristics	Power Supply	Battery Powered
	Battery Type	CR2450 x 1
	Typical Voltage	3 V
	Standard Battery Life	3 Years
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(WxHxD)	63.8 mm × 63.8 mm × 17.9 mm
	Weight	45.5 g
	Mounting Method	Wall
	Application Scenario	Indoor Green Keymat For Medical Application

ORDERING INFORMATION

114-264

Hikvision AX PRO Series Wall-mounted Wireless Emergency Button



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au